



| Model(50Hz) | Outlet |     | Motor power |      | Max head          | Max capacity        |      | Impeller passage | N.W  | G.W         | Packing dimension |
|-------------|--------|-----|-------------|------|-------------------|---------------------|------|------------------|------|-------------|-------------------|
|             | mm     | kW  | HP          | m    | m <sup>3</sup> /h | m <sup>3</sup> /min | mm   | kg               | kg   | mm          |                   |
| KBZ21.5     | 50     | 1.5 | 2           | 22   | 27.0              | 0.45                | 8.5  | 34.5             | 37.5 | 585X270X270 |                   |
| KBZ22.2     | 50     | 2.2 | 3           | 26.0 | 27.0              | 0.45                | 8.5  | 36               | 39   | 585X270X270 |                   |
| KBZ23.7     | 50     | 3.7 | 5           | 34.0 | 29.0              | 0.48                | 8.5  | 60               | 65   | 685X325X300 |                   |
| KBZ31.5     | 80     | 1.5 | 2           | 14.5 | 40.0              | 0.67                | 8.5  | 34.5             | 37   | 585X270X270 |                   |
| KBZ32.2     | 80     | 2.2 | 3           | 21.0 | 50.0              | 0.83                | 8.5  | 36               | 39   | 585X270X270 |                   |
| KBZ33.7     | 80     | 3.7 | 5           | 29.0 | 55.0              | 0.92                | 8.5  | 60               | 65   | 685X325X300 |                   |
| KBZ35.5     | 80     | 5.5 | 7.5         | 32.0 | 70.0              | 1.17                | 8.5  | 77               | 84   | 725X355X370 |                   |
| KBZ43.7     | 100    | 3.7 | 5           | 18.0 | 90.0              | 1.50                | 8.5  | 61               | 66   | 685X325X300 |                   |
| KBZ45.5     | 100    | 5.5 | 7.5         | 23.0 | 105.0             | 1.75                | 8.5  | 78               | 85   | 725X355X370 |                   |
| KBZ47.5     | 100    | 7.5 | 10          | 40.0 | 84.0              | 1.40                | 11.5 | 105              | 114  | 805X365X390 |                   |
| KBZ411      | 100    | 11  | 15          | 48.5 | 86.4              | 1.44                | 11.5 | 130              | 140  | 855X415X440 |                   |
| KBZ415      | 100    | 15  | 20          | 56.0 | 86.4              | 1.44                | 11.5 | 142              | 153  | 895X415X440 |                   |
| KBZ67.5     | 150    | 7.5 | 10          | 31.0 | 124.8             | 2.08                | 19.5 | 106              | 114  | 835X365X390 |                   |
| KBZ611      | 150    | 11  | 15          | 32.0 | 147.0             | 2.45                | 19.5 | 133              | 143  | 855X415X440 |                   |
| KBZ615      | 150    | 15  | 20          | 40.0 | 156.0             | 2.60                | 19.5 | 145              | 156  | 895X415X440 |                   |

