

LIKO LIGHTING S2010 SL

Performance Highlights

- An IP65 symmetrical and asymmetrical traditional floodlight complete with die-cast aluminium body and frame toughened glass cover. Reflector in pure aluminium with hammered surface.
- Provides easy installation and minimum maintenance with lamp compartment cover closing system by means of 2 screws. Suitable for HID 250W ~ 400W E40 lamps.

Performance Highlights

Electrical System:

- Built-in control gear suitable for HID lamp from 250W ~ 400W

Body Frame:

- Die-cast aluminium body

Reflector:

- Aluminium with hammered surface

Tempered Glass:

- Thermal resistant tempered glass

Mounting Bracket:

- Steel mounting bracket coated with epoxy powder

Technical Data

Ingress Protection:

- IP65

Voltage:

- 220 ~ 240Vac 50Hz

Lamp Type:

- Tubular

Lamp Watt:

- 250W ~ 400W

Holder Type:

- E40 ceramic holder

Maximum Weight:

- 9.0 kg

Color of Casing:



- Black



Application

- Stadiums & Beaches
- Harbours & Factories
- External High Rise Buildings
- Advertisement Signboards

Photometric



* Note: Photometric Result tested based on 26000 lm MH 250W tube.

Order Code

- S2010 ASY - M0250
- S2010 ASY - M0400
- S2010 SY - M0250
- S2010 SY - M0400
- S2010 ASY - S0250
- S2010 ASY - S0400
- S2010 SY - S0250
- S2010 SY - S0400

Dimension

