DYNATEC®
OIL

DYNATEC Compressor Oils VG68

DYNATEC Compressor Oils VG68 are advanced compressor oils, giving the best available performance in most of the oil-flooded air compressor of rotary or reciprocating type. They are formulated from highly refined premium quality base oil and selected additive system to provide exceptional performance an resistance to formation of deposit or valves, intercoolers and in compressor airways and they exceed the requirement of DIN 51506 CDL standards. They are available in ISO 32 through ISO 220 viscosity grades.

Model	VG6
VH	68
Density, g/ml @ 15°C	0.850
Kinematic Viscosity cSt@ (ASTM-D445) - 40°C	68
Kinematic Viscosity cSt@ (ASTM-D445) - 100°C	10.20
Flash Point °C	240
Nuetralization No, mgKOH/g	0.3
Viscosity index	135

Application

Dynatec Compressor Oils VG68 are suited to the following applications:

- Single-stage and multi-stage reci
- Procating or rotary air compressor with exhaust temperature up to 200°C
- Air or inert gas reciprocating compressors

Standard / Performance

- Reduce oil consumption, energy costs and extend oil change intervals
- Increase carbon free valve life
- Eliminate virtually all varbish, sludge and deposits.
- Retain high compressor efficiency and improve ignition safety factors substantially
- Eliminate need for seasonal oil changes.

Availability

Product is available in 1 litre and 4 litre.

Disclaimer of Liability

The information in this pds (product data sheet) was obtained from sources which we believe are reliable.However, the information is provided without any warranty, expressed or implied regarding, its correctness. Some information presented and conclusions drawnherein are from source other than direct test data on the substance itself. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. Users should make their own investigations to determine the suitablility of the information or product for their particular purpose.

The conditions or method of handling, storage, use and disposal of the product arebetond your control and may be beyond our knowledge. For this and others reasons, we do not assume reponsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

C-C™

No. 18, Jalan Marikh U5/177, Seksyen U5,
40150 Shah Alam, Selangor Darul Ehsan, Malaysia.
sales@concretecut.com.my
+603 78320743
+603 78323843